

# PRODUCT GUIDE



**BROOKS**<sup>®</sup>  
INSTRUMENT

Application Experience  
Beyond Measure

# Table of Contents



## Table of Contents

<b>Thermal Mass Flow Controllers and Meters</b> .....	4
– Multi-Purpose Mass Flow Controllers and Meters .....	5-6
– Ultra-High Purity Mass Flow Controllers and Meters .....	7
<b>Variable Area Flow Meters</b> .....	8
– Low-Flow Glass Tube Variable Area Meters .....	9
– Armored Metal Tube Variable Area Meters .....	10
– High-Flow Glass Tube Variable Area Meters .....	11
– Plastic Tube Variable Area Meters .....	12
– Precision Valves, Controllers, Switches and Indicators .....	13
<b>Pressure and Vacuum Products</b> .....	14
– Pressure/Vacuum Controllers .....	15
– Pressure Transducers and Transmitters .....	16
– Pressure Gauges, Regulators and Displays .....	17
– Vacuum Measurement .....	18
<b>Direct Liquid Injection Vaporizers</b> .....	19
<b>Coriolis Mass Flow Controllers and Meters</b> .....	21
<b>Secondary Electronics and Software Tools</b> .....	22
<b>Customized Systems and Solutions</b> .....	23
<b>Level Measurement</b> .....	24
<b>Point Level Measurement</b> .....	25
<b>Liquid Mass Flow Controllers and Oval Gear Meters</b> .....	26
.....	27



# Application Experience Beyond Measure



Every day, customers turn to Brooks Instrument for solutions to their flow, pressure, vacuum, vaporization and level challenges. Brooks' award-winning meters and controllers consistently rank at the top of their category for accuracy, reliability and user preference, as judged by the audience that matters - users of instrumentation. Brooks provides the broadest array of flow, pressure and level products in the market for a diverse range of industries:

- t Semiconductors
- t Chemical/petrochemical
- t Biopharmaceuticals
- t Solar cell
- t Fuel cell
- t Fiber optic
- t LED
- t Oil and gas
- t Analytical instrumentation
- t Power
- t Medical devices

But Brooks' products are only half the story. Our customers are backed by unsurpassed technical expertise around the planet. Local Brooks product and application specialists bring to each customer priceless application experience. They have been extensively trained to help you select the optimal solutions for your measurement and control needs, and offer years of experience solving application problems just like yours.

**When technology matters:** Brooks' revolutionary MultiFlo™ technology offers users of thermal mass flow products tremendous flexibility to satisfy a broad range of applications with one device.

**When quality matters:** A leading anesthesiology equipment supplier uses thousands of Brooks needle valves annually because of their precise, repeatable flow control and smooth 'feel.'

**When precision matters:** A Big 5 chemical company uses Brooks thermal mass and Quantim® Coriolis products exclusively for their critical catalyst and process research.

**When repeatability matters:** Many leading biotechnology companies use only Brooks thermal mass flow controllers as the standard for bench-top reactors and full production units to ensure smooth scale-up.


**When consistent performance over a wide range of flows matters:** Leading fuel cell companies worldwide specify Brooks thermal mass flow controllers for their exceptional accuracy, wide turn-down and response time.

**When global reach matters:** Leading engineering contractors select Brooks variable area meters for multi-national projects that require compliance with worldwide standards because of Brooks' local experience and global support.

**When certifications matter:** Many Brooks products are available with national laboratory calibration traceability, ISO 9001 certification, recognized hazardous area approvals, and CE, FDA, and other international certifications.

So if you're looking for a solution, our products are the answer through our global network of distributors and service centers.

# Thermal Mass Flow Controllers and Meters



## The most popular thermal mass flow product line on the planet!

Brooks offers a broad range of thermal mass flow controllers (MFCs) and meters, ensuring that we will have exactly the right device for your application. Our mass flow controllers are the acknowledged industry leader in quality and reliability, with many devices in operation for more than 20 years.

Brooks thermal mass flow devices provide significant advantages in long term stability, response time, accuracy, repeatability, turndown, self-diagnostics and application flexibility. The Brooks portfolio covers the widest range of options to meet your application needs, including:

- t Pressure transient insensitive MFCs (an industry first)
- t MultiFlo™ (i.e., multi-gas and multi-range) capability to satisfy a broad range of applications with one device without removing device from system (an industry first)
- t FOUNDATION™ Fieldbus communications option
- t NEMA 4X/IP66 MFCs for hose down/wash down applications (an industry first)
- t Ultra-high purity devices for the vacuum, thin film, solar and semiconductor industry
- t Class 1 Div 2 / Zone 2 approved devices for use in hazardous areas
- t Downport MFCs for ease of maintenance and reduced gas panel footprint

Plus, we have the best trained and most responsive flow experts with application experience in virtually every industry, all over the world. They make sure your thermal mass flow controller is selected correctly and maintained properly.

### Applications include:



Awards	Communications Options
 Reader's Choice Award for best products in the "Flowmeter, Thermal Mass" category.	  
 Golden gas Award winner in "Mass Flow Measurement & Control" for the GF Series.	

# Multi-Purpose Mass Flow Controllers and Meters



SLA5800 Series



SLAMf™ Series

## SLA Series mass flow measurement and control

The Smart Link Advantage (SLA) Series is Brooks' premier smart digital thermal mass flow series. SLA mass flow controllers and mass flow meters link to advanced service tools and offer the advantage of digital protocols. The SLA Series provides many advanced features such as enhanced long term stability, improved turndown, and more.

The Brooks SLAMf™ Series mass flow line is designed specifically for use in harsh environments. Their unique NEMA 4X/IP66 enclosure™ provides protection from dust and water making them ideal for indoor or outdoor use and perfect for hose down/wash down applications. The integrated sensor, valve and PID make these devices a cost-effective solution for hazardous area installations.

- t Faster response, better accuracy and improved control over analog devices
- t Industry-leading repeatability ensures a stable process even under changing conditions
- t Self diagnostics and alarms eliminate downtime
- t Multiple communication protocols allow easy integration into many control systems
- t Analog I/O devices allow for quick and easy system integration
- t Elastomer seal option provides exceptional leak integrity and maximizes control valve shutoff dependability
- t Globally approved for a variety of service areas

Type	Model	Full-Scale Capacity N <sub>2</sub> Eq.	Max. Pressure psig (barg)	Accuracy	Input/Output	Power Supply
Elastomer Seal Controller/Meter	SLA5800 Series	3 sccm - 2500 slpm	4500 (310)	0.9% rate	0(1) - 5 Vdc / 0-10 Vdc / 0(4) - 20 mA RS485 / DeviceNet <sup>®</sup> / Profibus / FOUNDATION™ Fieldbus	11 - 27 Vdc (see data sheet)
NEMA 4X/IP66 Elastomer Seal Controller/Meter	SLAMf Series	3 sccm - 2500 slpm	4500 (310)	0.9% rate	0(1) - 5 Vdc / 0-10 Vdc / 0(4) - 20 mA RS485 / DeviceNet <sup>®</sup> / Profibus / FOUNDATION™ Fieldbus	11 - 27 Vdc (see data sheet)
NEMA 4X/IP66 Elastomer Seal Controller/Meter	MF64S	3 sccm - 36000 slpm	1500 (100)	1% FS	Profibus	15-24 vdc



# Multi-Purpose Mass Flow Controllers and Meters



GF40/80 Series

4800 Series

5850E Series

## GF40/80 Series mass flow measurement and control

Designed for solar thin film deposition, CVD, vacuum processes, bioreactors and other industrial gas flow control applications that require cost-efficient solutions.

- t NEW high flow rate option (up to 300 slpm) designed with a compact footprint
- t Fast sub 1 second settling time
- t MultiFlo™ gas and range configurability
- t Corrosion-resistant Hastelloy sensor tube

## 4800 Series mass flow measurement and control

Featuring a broad flow range, compact size and MEMS-based sensor that provides lightning-fast response times.

## E and I Series mass flow measurement and control

For those that do not require the super high performance and accuracy of a digital mass flow meter, Brooks offers reliable analog mass flow controllers and meter. These devices continue to add to their expansive installed base due to their good response, accuracy, and simple integration.

Type	Model	Full-Scale Capacity N <sub>2</sub> Eq.	Max. Pressure psig (barg)	Accuracy	Input/Output	Power Supply
Elastomer Seal Controller/Meter	GF40	3 sccm - 50 slpm	150 (10)	±1% rate	0-5 Vdc / 0-10 Vdc / 0-20mA, 4-20 mA / Profibus / RS485 / DeviceNet™ / EtherCAT®	11 - 27Vdc (see data sheet)
	GF80	3 sccm - 50 slpm	150 (10)	±1% rate	0-5 Vdc / 0-10 Vdc / 0-20mA, 4-20 mA / Profibus / RS485 / DeviceNet™ / EtherCAT®	11 - 27Vdc (see data sheet)
Metal Seal Controller/Meter	GF81	51 slpm - 300 slpm	Meter: 75 (5) Controller: 150 (10)			
Elastomer Seal Controller/Meter	4800 Series	50 sccm - 40 slpm	150 (10)	±1% FS or ±3% FS	0 - 5 Vdc / 4 - 20 mA RS232	15 - 24Vdc
	5800S	3 sccm - 2500 slpm	4500 (310)	0.9% rate & ±0.2% FS	Profibus	15 - 24Vdc
			(100)	1% FS	0 - 5 Vdc	+/-15Vdc
			0 (100)	1% FS	0 - 5 Vdc / 4 - 20 mA	15 - 24Vdc
			00 (100)	1% FS	0 - 5 Vdc / 4 - 20 mA	+/-15Vdc or 15 - 24 Vdc







GF100 Series

GF100 Series High Flow

GF135

## GF100 Series mass flow measurement and control

Designed for semiconductor, MOCVD and other gas flow control applications that require a high-purity, all-metal flow path, the GF Series delivers outstanding performance, reliability and flexibility. The GF Series has been marathon-tested to over three times the semiconductor industry standard for reliability, ensuring repeatable low-drift performance over time.

- t Ultra-fast 300-millisecond settling time
- t Optional pressure transient insensitive (PTI), high accuracy and safe delivery system models available
- t New high flow rate options (up to 300 slpm) designed for high-flow purge, EPI and blanket gas control applications
- t MultiFlo™ gas and range configurability
- t Corrosion-resistant Hastelloy® sensor tube and valve orifice (jet)

## GF135 Advanced Diagnostics mass flow controller

Designed for the next step in semiconductor etch, thin film and other advanced process gas control applications, the GF135 combines all of the benefits provided by the most advanced pressure transient insensitive mass flow controller (MFC) and adds real-time flow error detection with advanced diagnostics.

Type	Model	Full-Scale Capacity	Max. Pressure psig (bar)	Accuracy	Input/Output	Power Supply
HP Metal Seal Controller/Meter	GF100	3 sccm - 300 slpm N <sub>2</sub> equivalent	485 (33)	±1% rate (35-100% FS)	0 - 5 Vdc / RS485 / DeviceNet™	±15 Vdc, ±24 Vdc, 11-25 Vdc
	GF101		100 (5)			
UHP Metal Seal Controller/Meter	GF120	3 sccm - 300 slpm N <sub>2</sub> equivalent	485 (33)	±1% rate (35-100% FS)	0 - 5 Vdc / RS485 / DeviceNet™	±15 Vdc, ±24 Vdc, 11-25 Vdc
	GF121		100 (5)			
UHP Safe Delivery Metal Seal Controller	GF120 (SDS)	4 sccm - 1 slpm	485 (33)	±1% rate (35-100% FS)	0 - 5 Vdc / RS485 / DeviceNet™	±15 Vdc, ±24 Vdc, 11-25 Vdc
UHP PTI Metal Seal Controller	GF125	3 sccm - 300 slpm N <sub>2</sub> equivalent	85 (6)	±1% rate (35-100% FS)	0 - 5 Vdc / RS485 / DeviceNet™	±15 Vdc, ±24 Vdc, 11-25 Vdc
	GF 126		75 (5)			
UHP High-Accuracy Metal Seal Controller/Meter	GF125 (HA)	5 sccm - 10 slpm N <sub>2</sub> equivalent	85 (6)	±1% rate (35-100% FS)	0 - 5 Vdc / RS485 / DeviceNet™	±15 Vdc, ±24 Vdc, 11-25 Vdc
PTI Metal Seal Controller	GF 135	3 sccm - 5 slpm N <sub>2</sub> equivalent	85 (6)	±1% rate (35-100% FS)	0 - 5 Vdc / RS485 / DeviceNet™	±15 Vdc, ±24 Vdc, 11-25 Vdc



# Variable Area Flow Meters



## Over sixty years of variable area meter expertise

Brooks started designing and manufacturing variable area (VA) meters, also referred to as rotameters, in 1946. Now, with more than six decades of application experience, we help customers with VA solutions in just about every industry. Our solutions have come from our standard portfolio as well as custom-designed products incorporating special materials of construction, connections and pressure ratings.



The Brooks line of glass tube and metal tube VA meters ensures measurement repeatability, which provides dependable flow monitoring and consistency. External power is not required for operation; therefore, they provide a fail-safe flow indication under any circumstance. Brooks VA meters can be provided with a variety of wetted materials for high-pressure, high-temperature conditions and hazardous locations.

**Armored VA Meters:** The Brooks line of rugged metal tube VA flow meters is ideal for high-pressure, high-temperature, and other demanding flow applications where safety is a concern. HART, FOUNDATION™ Fieldbus and 4 - 20 mA outputs and limit switches provide for remote flow monitoring.

**Glass Tube VA Meters:** The Brooks line of reliable glass tube VA meters is ideal for gas and liquid flow measuring applications where viewing the process is desirable.

**Purgemeters:** The Brooks Sho-Rate™ brand of VA meters delivers industry-leading performance for gas or liquid flows. Robust engineering ensures reliable indication and unsurpassed service life.

### Applications include:





# Low-Flow Glass Tube Variable Area Meters



1350 Sho-Rate™



1358 Sho-Rate™



1250 Sho-Rate™

The name Sho-Rate™ has meant reliability and performance for decades now, and the 1350 and 1355 Sho-Rate variable area meters continue to deliver industry-leading performance for gas or liquid flows today. Their robust and proven engineering ensures reliable indication and unsurpassed service life. Sho-Rate flow meters pioneered the concept of field-replaceable tube and float kits; the tube and float can be replaced in-line, if necessary, in a matter of minutes. Our 1250/1255 Sho-Rate models offer an easy-to-read rotating magnifying glass, making it the ideal choice for display on panels and cabinets.

## 1350/1355 Sho-Rate

*Rugged and durable*

- t Integral needle valves on inlet or outlet
- t Integral flow controller that compensates for varying inlet or outlet pressures
- t 316 stainless, brass, or Kynar™ construction
- t Custom scales for any application

## 1250/1255 Sho-Rate

*Ideal for panel display*

- t Integral needle valves on inlet or outlet
- t Direct-read scales for common units and fluids
- t Easy-change design allows quick interchangeability of tube assemblies
- t Rotating lens allows 180° view with magnification

Model	Capacity – Water		Capacity – Air		Accuracy	Max. Pressure psig (bar)	Construction
	(lph)	(gph)	(m <sup>3</sup> /hr)	(scfm)			
1350/1355 Sho-Rate	0.041-130	0.010 - 34	0.003-3.9	0.002 - 2.33	5% (1350) FS; 3% (1355) FS	200 (14)	Glass tube w/ brass, 316SS, or Kynar
1358 Sho-Rate	180 - 1000	49 - 280	5.7 - 22	3.4 - 15	10% FS	200 (14)	Glass tube w/ brass or 316 SS
1250/1255 Sho-Rate	1.3 - 120	0.34 - 32	0.003 - 3.9	0.001 - 2.33	10% (1250) FS 5% (1255) FS	200 (14)	Glass tube w/ aluminum or 316 SS

# Armored Metal Tube Variable Area Meters



MT3809 XP Flameproof

MT3809 Indicator Only

3750 Ar-Mite

The Brooks line of rugged metal tube variable area meters (rotameters) is ideal for high-pressure, high-temperature and other demanding flow applications where safety is a concern.

- t Accuracy across an ultra-wide range of flow rates and temperatures
- t Globally approved for use in hazardous environments
- t Needle valves available for flow control
- t Multiple connection options to match your existing system and provide easy installation
- t Many corrosion-resistant material options for the metering of aggressive fluids
- t Alarm and 4 - 20 mA with HART and  $\mu$ PROF<sup>SM</sup> Fieldbus options provide for remote flow monitoring
- t Excellent meter repeatability provides consistent batch and/or process production
- t No power required, which reduces installation cost and provides flow measurement in hazardous areas
- t Low-pressure drop

Model	Capacity – Water		Capacity – Air		Accuracy rate	Max. Pressure		Temperature		Output
	(lph)	(gpm)	(m <sup>3</sup> /hr)	(scfm)		bar	psig	C	F	
3600 Series	18 - 11355	0.08 - 50	0.65 - 43	0.38 - 28	10%	103	1500	-29 - 204	-20 - 400	Alarm (IS or X-Proof)
3750	0.8 - 100	0.03 - 44	0.04 - 3.1	0.02 - 2	5%	275	4000	-29 - 204	-20 - 400	Alarm and/or 4-20 mA (IS or X-Proof)
MT3809	25 - 100,000	0.11 - 440	0.78 - 1404	0.49 - 888	2%	413	6000	-198 - 420	-325 - 788	Alarm and/or 4-20 mA, HART (IS or X-Proof)
MT3810	25 - 20,000	0.11 - 88	0.78 - 620	0.49 - 392	5%	103	1500	-29 - 215	-20 - 420	Alarm and/or 4-20 mA, HART (IS or X-Proof)
MT3819	110 - 15,000	0.48 - 66	3.2 - 432	2 - 275	2%	19	275	-29 - 150	-20 - 300	Alarm and/or 4-20 mA, HART (IS or X-Proof)

<sup>1</sup> Special designs for flow rates as low as 5 l/h of air and 0.08 l/h of water are available. Consult your local representative for more information.

<sup>2</sup> Special designs for up to 15,000 psi (1000 bar) are available. Consult your local representative for more information.



# High-Flow Glass Tube Variable Area Meters



GT1000



GT1305

The Brooks line of reliable glass tube variable area meters (rotameters) is ideal for many gas and liquid flow measuring applications where viewing the process is important.

- t Tube and float can be re-ranged in-line, minimizing process downtime
- t Rotatable connections for easy installation at any angle
- t O-ring sealing to meet piping requirements or customer preference
- t Globally approved for use in hazardous environments
- t Reliable - only one moving part
- t No power required, which reduces installation cost and provides flow measurement in hazardous areas
- t Low-pressure drop allows for economical pump selection
- t Flow alarms available on some models
- t Rugged, vented polycarbonate enclosure available on most models

Model	Capacity – Water		Capacity – Air		Accuracy	Max. Pressure psig (bar)	Output
	(lph)	(gpm)	(m <sup>3</sup> /hr)	(scfm)			
GT1000	0.032 - 22,000	0.0001 - 98	0.002 - 280	0.001 - 170	2% FS	500 (34)	Alarm (IS)
GT1307	39 - 20900	0.17 - 92	1.5 - 342	0.9 - 217	2% FS	350 (24)	Local Indication Only
GT1305	185 - 11355	0.8 - 50	4.7 - 79	3 - 50	10% FS	200 (14)	Alarm



# Plastic Tube Variable Area Meters



2510

2520

2540

Brooks Instrument's versatile, economic acrylic flow meters are ideal for a variety of air, water and gas flow instrumentation applications. The new Series 2500 is a standard precision-machined acrylic flow meter for liquids and gases. It has direct-read air or water scales and is available in either English or metric scales. Series 2500 devices can be configured with various control valve, fitting and O-ring options.

- t Easy-to-read English or metric scales
- t Water ranges from 4 ccm to 20 gpm
- t Air ranges from 40 ccm to 4000 slpm
- t Threaded brass inserts for quick installation
- t Easy disassembly and assembly for maintenance
- t Durable one-piece clear acrylic construction
- t Stable, easy-to-read float

Model	Capacity – Water		Capacity – Air		Accuracy	Max. Pressure psig (bar)	Temperature °C (°F)	Construction
	(lph)	(gph)	(m <sup>3</sup> /hr)	(scfm)				
2510	8 - 150	.2 - 40	.002 - 5.5	.002 - 3.3	5% FS	100 (6.8)	65 (150)	Plastic tube w/ brass or 316 SS
2520	4 - 220	1 - 60	.002 - 5.5	.002 - 3.3	3% FS	100 (6.8)	65 (150)	Plastic tube w/ brass or 316 SS
2530	45 - 1130	12 - 300	.76 - 30	.5 - 20	3% FS	100 (6.8)	65 (150)	Plastic tube w/ brass or 316 SS
2540-S/2540-V /2540-I	90 - 4500	24 - 1200	5.5 - 165	3 - 100	2% FS	100 (6.8)	65 (150)	Plastic tube w/ PVC or 316 SS



FC8800 Series

with 1355 Sho-Rate™



8500 Series NRS™



1198

## Manual Flow Controller

Brooks Model FC8800/8900 Series flow controllers are designed to maintain a constant differential pressure across an integral manual flow regulating valve.

- t Series 8800 controllers are designed for all liquid and gas flows with variable upstream pressures.
- t Series 8900 controllers are for all liquid and gas flows with variable downstream pressures.

## Control Valve, Fine Control

Brooks Model 8500 Series NRS™ (non-rising stem) control valves are designed specifically for extremely low-flow gas and liquid applications. Straight and 90° angle models in brass and stainless steel are available. They feature a means of adjusting a sliding tapered needle, which prevents sticking. These valves are particularly suitable for precise control and possess a high turns-to-lift ratio. The flow is constant for any given stem position.

## Flow Switch

The CCB311 flow switch is designed to detect low flows in horizontal or vertical pipes with an upward flow direction. Suitable for liquids or gases, the CCB311 flow switch is very robust with high repeatability and a very basic design. It is certified explosion proof / intrinsically safe.

## Flow Indicator

Brooks Instrument Model 1198 flow indicators provide a quick, reliable and economical way to verify fluid flows through industrial process lines. Model 1198 is available with three styles of indicators including paddle wheel, flap style or drip tube/whistle shape. Many specials are also available upon request to meet various conditions of pressure, temperature, fluid types and mechanical dimensions.

# Pressure and Vacuum Products



## Measuring pressure and vacuum with superior design and performance

Brooks now offers a very diverse line of pressure and vacuum products including pressure/vacuum controllers, pressure gauges, pressure transducers, pressure transmitters, pressure regulators, capacitance manometers, and more.

- t Pressure/vacuum controllers that are flexible enough to manage the pressure of gas or liquid upstream or downstream of the device
- t Pressure gauges that meet rigid cleanliness and safety guidelines
- t Remote transducers that provide stability and reliability using proven sensing technologies
- t All-PFAseal-free pressure transducers for measurement of ultra-high purity fluids including corrosives
- t Compact and economical high-precision mechanical pressure regulators
- t Heated and unheated capacitance manometers that meet the diverse requirements of vacuum-based processes

## Cylinder Scales

The GCS400 Series cylinder scales are used to accurately measure the remaining mass of liquid or gas in supply vessels. They employ a sealed load cell and heavy gauge stainless steel housing for exceptional durability and reliability in all applications. The GCS400 Series are additionally certified intrinsically safe for use in NEC Class I, Division 1 hazardous areas.



Model	Capacity	Output	Compliance
	lbs	4-20 mA 0.05-5.05 Vdc	CE



# Pressure/Vacuum Controllers



SLA7810/20 Series



SLA5810/20 Elastomer Series



Model 5866RT

Electronic pressure controllers manage the pressure of gas upstream or downstream of the device. Brooks electronic pressure controllers utilize the core control technology present in our industry-leading thermal mass flow controllers.

Brooks replaces the thermal mass flow sensor with a pressure sensor, provides industry-leading control valve technology and software, then controls the pressure of a fluid based on a set-point signal to the device. Using a closed-loop control, Brooks pressure controllers do not have the droop or hysteresis associated with traditional mechanical spring diaphragm pressure regulators. Brooks pressure controllers are available with internal pressure sensors to control pressure in a range from vacuum to 4500 psia.

Brooks pressure controllers can be configured to use external pressure sensors for added flexibility. When using an external pressure sensor, the flow of the gas required to maintain pressure can be controlled and measured.

Type	Model	Full-Scale Capacity	Pressure Accuracy	Max. Pressure psia (bara)	Input/Output	Power Supply
<b>Pressure Controllers</b>						
Metal Seal, 1.125"	SLA7810/20	0 - 290 psia (0 - 20 bara)	0.5% FS	290 (20)	0 - 5 Vdc / DeviceNet™	11 - 25 Vdc (see data sheet)
Elastomer Seal	SLA5810/20 Series	0-4500 psia (0-310 bara)	±0.25% FS (>300 psia) ±0.12% FS (<300 psia)	4500 (310)	0(1) - 5 Vdc / 0-10 Vdc / 0(4) - 20 mA RS485 / Profibus / FOUNDATION Fieldbus	11-27 Vdc (see data sheet)
Elastomer Seal	SLAMf 10/20	0-4500 psia (0-310 bara)	±0.25% FS (>300 psia) ±0.12% FS (<300 psia)	4500 (310)	0(1) - 5 Vdc / 0-10 Vdc / 0(4) - 20 mA RS485 / Profibus	11-27 Vdc (see data sheet)

Type	Model	Full-Scale Capacity N <sub>2</sub>	Flow Accuracy	Max. Pressure psia (barg)	Input/Output	Power Supply
<b>Remote Transducers/Pressure Controlling Flow Meters</b>						
Metal Seal, 1.125"	SLA7840	3 sccm - 30 slpm	1% Rate	1500 (100)	DeviceNet	11 - 25 Vdc (see data sheet)
Elastomer Seal	SLA5840 Series	3 sccm - 50 slpm	0.9% Rate	4500 (310)	0(1) - 5 Vdc / 0-10 Vdc / 0(4) - 20 mA RS485 / Profibus / FOUNDATION Fieldbus	11-27 Vdc (see data sheet)
Elastomer Seal	5866RT	3 sccm - 30 slpm	1% FS	1500 (100)	0(1) - 5 Vdc / 0-10 Vdc / 0(4) - 20 mA RS485 / Profibus	11-27 Vdc (see data sheet)

# Pressure Transducers and Transmitters



SolidSense II™

SolidSense II™ ATEX

Seal-Free Pressure (SFP) Transmitter

## Ultra-High Purity Pressure Transducers

The Brooks SolidSense II® ultra-high purity pressure transducers offer the lowest cost of ownership for high-purity gas distribution systems through virtually zero-maintenance operations. The ultra-stable, micro-machined silicon strain gauges are matched and glass-fused at high temperature to the metal diaphragm. This process reduces drift commonly associated with competitive products. These transducers will not need to be reset immediately after installation and will not temporarily indicate inaccurate pressure readings during purge cycle.

Model	Full-Scale Range	Pressure Reference	Output	Electrical Connection
SolidSense II	30 - 3000 psi	Absolute, gauge or compound	4 - 20 mA, 0 - 10 Vdc, 0.05 - 5.05 Vdc	Bendix, Pigtail, 15-pin D-sub

\*More configurations available upon request. Contact your local Brooks representative.

## Industrial Pressure Transmitters

The Brooks SolidSense II® ATEX industrial pressure transmitters offer superior corrosion resistance with a 316L VIM-VAR stainless steel, chromium-enriched wetted flow path, making them suitable for virtually all process fluids. Active temperature compensation enables improved process pressure measurement in plants exposed to wide temperature variations. High accuracy, combined with FM and ATEX compliance, makes the SolidSense II ATEX pressure transmitter the optimum choice for demanding applications.

Model	Full-Scale Range	Pressure Reference	Output	Electrical Connection
Solid Sense II ATEX	30 - 3000 psi	Absolute, gauge or compound	4 - 20 mA (others available upon request)	Pigtail

\*More configurations available upon request. Contact your local Brooks representative.

## Polymer Pressure Transmitters

The Brooks SFP polymer pressure transmitters use a seal-free perfluoroalkoxy (PFA) sensor to eliminate the potential for process fluid contamination. A temperature-compensated output ensures repeatable pressure measurement and a leak indicator provides visual warning of potentially unsafe operation.

Model	Full-Scale Range	Pressure Reference	Output	Electrical Connection
SFP Transmitter	30 - 3000 psi	Absolute, gauge, compound	4 - 20 mA (others available upon request)	Pigtail

# Pressure Gauges, Regulators and Displays



S122/C122/F122Series

LR056 Pressure Display

8601 Pressure Regulator

## Pressure Gauges

Brooks Instrument pressure gauges feature all-stainless wetted materials and are welded in an oxygen-free environment to meet rigid cleanliness and safety guidelines for all demanding requirements, including high-purity gases. An optional transmitting alarm or continuous transmitter enhances the versatility of Brooks' pressure gauges in applications where automation is required.

Model	Range	Accuracy	Process Connections
S122/C122/F1222" Pressure Gauges	Vacuum to 4,000 psig	1% FS	Face seal male/female, NPT
IPS122 2" Indicating Pressure Switches	Vacuum to 4,000 psig	1% FS	Face seal male/female, NPT
IPT122 2" Indicating Pressure Transmitters	Vacuum to 4,000 psig	1% FS	Face seal male/female, NPT

## Pressure Regulators

Brooks 8601 high-precision supply pressure regulators are direct-acting, non-relieving units that provide bubble-tight shut-off on helium at 100psi. Compact and economical, these units are assembled in a cleanroom environment and are tested under simulated operating conditions.

Type	Model	Full-Scale Capacity	Max. Pressure	Temperature	Construction
Pressure Regulator	8601	3 - 1000 ccm Air	250 psig, 17 bar	1 - 177 °C 33 - 350 °F	Aluminum, 316 SS

## Pressure Displays

Brooks offers a new generation of displays for our SolidSense II pressure transducers or other pressure devices that provide 4 - 20mA analog communication. Displayed pressure units and ranges are user-settable. The LR056 series also provides two user-programmable alarms for high or low pressure condition.





XacTorr™ CMX Series

CMC Series

## Rugged, stable capacitance manometers

Brooks capacitance manometers incorporate industry-leading features that combine to improve measurement reliability, minimize drift, resist diaphragm contamination and minimize thermal effects. The result is an exceptionally reliable capacitance manometer family for all vacuum measurement applications.

An important benefit of a Brooks XacTorr is its advanced Mark-IV sensor. The sensor chamber contains surface areas that are not used in the pressure measurement; these surfaces provide locations for particles and condensable vapors to accumulate without affecting the sensor, dramatically reducing the need for re-zeroing and greatly extending sensor life. The sensor diaphragm is made from corrosion-resistant Inconel®.

### XacTorr™ CMX Series

The XacTorr CMX series gauges are premium heated gauges that use patented, dual-zone heating to ensure 0.1 °C temperature uniformity. The sensor very quickly recovers from thermal events and is virtually immune to ambient temperature changes. Three operating temperatures are offered, 45 °C, 100 °C and 160 °C, with full-scale measurement ranges from 100 milli Torr to 1000 Torr. An unheated configuration is available for applications that require high vacuum (<10 Torr Full Scale) or DeviceNet communication.

Model	Ranges FS (Torr)	Measurement Range	Operating Temp (°C)	Accuracy Sub 1/1-100/1000 Torr Ranges	Temp. Coefficient	Input/Output
CMX0	1, 2, 10, 20, 100, 1000	4 decades (from FS)	Ambient	0.25% of reading	0.002% of FS/°C (zero)/ 0.02% of FX/°C (span)	RS485, DeviceNet, Analog
CMX45	0.1, 0.5, 1, 2, 10, 20, 100, 1000	4 decades (from FS)	45	0.25% or 0.50% of reading/ 0.15% of reading	0.002% of FS/°C (zero)/ 0.02% of FX/°C (span)	RS485, DeviceNet, Analog
CMX100	0.1, 0.5, 1, 2, 10, 20, 100, 1000	4 decades (from FS)	100	0.25% of reading/ 0.15% of reading	0.002% of FS/°C (zero)/ 0.02% of FX/°C (span)	RS485, DeviceNet, Analog
CMX160	1, 2, 10, 20, 100, 1000	4 decades (from FS)	160	0.50% of reading / 0.25 to 0.35% of reading	0.002% of FS/°C (zero)/ 0.02% of FX/°C (span)	RS485, DeviceNet, Analog

### CMC (Unheated Gauges)

CMC series gauges are compact, economical un-heated capacitance manometers that feature a robust all-welded Inconel® sensing diaphragm. The device's electronics are temperature compensated to minimize

Model	Range FS (Torr)	Measurement Range	Operating Temp. (°C)	Accuracy	Temp. Coefficient	Output Signal
	20	(75)	Unheated	0.25% or 0.50% of reading	0.005% of FS/°C (zero) 0.027% of FX/°C (span)	0-10 vdc



Direct Liquid Injection Vaporizer



Integrated System

## Break free from conventional vaporizing technology

Direct liquid injection (DLI) vaporization solutions are high-performing liquid vaporizers designed for customers who require reliable liquid vaporization. Direct liquid injection vaporizers overcome the many limitations of conventional vaporizing systems, such as bubblers and vapor draw systems, for more efficiency, control and precision.

The Brooks DLI vaporizers employ hot gas, rather than a hot metal surface, to accomplish liquid vaporization. With unique atomization and heat exchanger technology, the Brooks DLI vaporizers deliver chemically pure vapor and provide enhanced thermal, optical and hardness characteristics for various applications:

- t Water vaporization for fuel cell stack humidification and many other water addition applications
- t Liquid precursor vaporization for chemical vapor deposition (CVD), metal oxide chemical vapor deposition (MOCVD), and atomic layer deposition (ALD)
- t Depositing thin films for enhanced thermal, optical or hardness characteristics such as diamond-like carbon coating and glass coating
- t Vaporizing monomers for vacuum polymer film deposition
- t Generating calibration vapor
- t Vaporizing liquid hydrocarbons

### Specifications:

- t Allowable process pressure: vacuum to many atmospheres
- t Vapor capacity: less than 5g per hour to greater than 15kg per hour. (In calibration vapor applications, the target analyte concentrations may be achieved proportioning the liquid and carrier gas flows.)
- t Number of liquid feeds: multiple
- t Sample wetted materials: 316L stainless steel with elastomer seals, all welded 316L, electropolished 316L with nickel seals
- t Vaporizer chamber heating: electric band heater
- t Heater power: less than 100 W to greater than 5000 W, application dependent; 100 Vac, 115 Vac or 230 Vac
- t Temperature sensors: two K-type thermocouples, one for chamber temperature and one for over-temperature alarm
- t Process connections: 1/8" to 1" compression, face-seal or NPT type
- t Leak integrity:  $1 \times 10^{-9}$  cc/sec helium
- t Dimensions: vary by application. A 400 W DLI vaporizer is approximately 200 mm x 125 mm x 125 mm

# Coriolis Mass Flow Controllers and Meters



## The first Coriolis device with built-in control

Quantim® is the first miniaturized Coriolis mass flow controller that measures and controls flow directly without any need to compensate for fluid properties or process conditions. Quantim's Coriolis technology, internal control valve and PID bring a new level of measurement accuracy and control all in one compact package.

The Coriolis principle is not new to process flow measurement. It is a proven technology that has been employed in a wide variety of markets and applications for over 30 years. Although Coriolis has been widely used in high-flow processes, Quantim brings precise flow measurement and control to lower-flow applications.

Quantim Coriolis controllers and meters provide unsurpassed performance, reliability, repeatability and control in demanding low-flow applications. The Brooks Coriolis portfolio covers virtually every need you may have, including:

- t Metal seal devices for the vacuum thin film and semiconductor industry
- t NEMA 4X/IP66 MFCs for wash down applications
- t Downport MFCs for installation and service ease
- t High-pressure capability for demanding research applications

Our products also have an array of certifications and approvals for ingress protection and use in hazardous areas. Plus, we have the best trained and most responsive flow experts with application experience in virtually every industry, all over the world. They make sure your Coriolis mass flow device is selected correctly and maintained properly.

Applications include:



# Coriolis Mass Flow Controllers and Meters



QMBC IP40



QMBC IP66

Brooks Quantim Coriolis mass flow controllers and meters offer unsurpassed accuracy and flexibility in critical low-flow liquid and gas applications.

The heart of the device is a patented Coriolis sensor design that measures low flows independent of the fluid type or process variables. This provides you with unsurpassed performance, repeatable mass flow measurement and control even under changing conditions.

Brooks Quantim products are some of the smallest, lowest-flow Coriolis meters and controllers available on the market. With a footprint the size of a netbook, you can fit this instrument into any tight space.

Coriolis meters and controllers are available in NEMA 1/IP40, NEMA 4X/IP66, explosion proof and ANSI/ISA-76 downport configurations.

Type	Model	Tube Size	Nominal Flow* liquid (kg/hr)/gas (lpm)	Accuracy	Max. Pressure psig (bar)	Input/Output
Precision Mass Flow Controller Gas and Liquid	QMBC	2	0.15/1.05	+/-0.2%, 0.5% or 1% rate	500 (35), 1500 (100) or 4500 (300)	0 - 5 Vdc, 4 - 20 mA or HART
		3	0.78/2.96			
		4	7.97/24.8			
Precision Mass Flow Meter Gas and Liquid	QMBM	2	0.19/1.43	+/-0.2%, 0.5% or 1% rate	500 (35), 1500 (100) or 4500 (300)	0 - 5 Vdc, 4 - 20 mA or HART
		3	1.00/5.60			
		4	13.5/53.1			



\* Higher flows may be possible depending on the fluid and process conditions.





Model 0254



Model 0260



Brooks Service Suite

## Model 0254 four-channel power supply, readout and set-point controller

The Brooks 0254 is an innovative, reliable microcomputer-based controller that provides power for up to four Brooks mass flow meters and controllers, and/or pressure devices, all in a new compact design. Additionally, the 0254 can generate flow set-point commands, display flow rate, totalize flow, batch, blend multiple flow streams and more. This fully RoHS-compliant device has a very user-friendly operation and is offered with multiple mounting options such as rack mount, panel mount and table-top mount.

## Brooks Smart Interface Model 0260 controls and monitors up to 30 devices

The Brooks Smart Interface Model 0260 is a Microsoft Windows®-based software application that provides expanded control and monitoring capabilities in laboratory and research environments for Brooks thermal mass flow meters and controllers with an RS485 Smart protocol digital interface. Together with the power supply and RS485 to USB hardware module, this product is a great solution for monitoring and controlling up to 30 mass flow meters/controllers.

Model	Channels	Additional Functions	Control I/O	Power Input	Power Output
0254	4	Totalize and blend RS-232I/O for remote control	1 - 5 Vdc, 2 - 10 Vdc, 4 - 20 mA	100 - 240 Vac, 50/60 Hz	+/-15 Vdc, 24 Vdc
0260	Up to 30 devices	Display flow, adjust set point, display alarm status, display and change valve override (VOR) status, totalize, batch, blend, log data	RS485 Smart Protocol	85 - 250 Vac, 47 - 63 Hz	24 Vdc, 3.5 A

## Brooks Service Suite

Brooks Instrument provides a variety of software and accessory options to simplify installations and start-up. Brooks software tools ensure mass flow controllers perform at their best. Calibration and control software, available for all Brooks mass flow meters, allows users to perform calibration checks to verify accuracy and repeatability.

The Brooks Service Suite software provides I/O tuning, alarm indication/configuration, diagnostics, and data logging capabilities.

The Brooks Service Suite software provides I/O tuning, alarm indication/configuration, diagnostics, selected data logging, and accuracy reporting capabilities.



MT3809 Special



Manifold Solution

## Custom engineering for special applications

Can't find the exact instrument for your application? Let Brooks' application experts devise a custom solution for you. Our expertise in custom-engineered flow products for unique applications includes:

- t Special ambient requirements
- t High/low process temperature operation
- t Exotic materials
- t High process pressure capability
- t Difficult process streams

If you have a unique application, contact Brooks or your local sales representative.

### Comprehensive Solutions

Customers tight on resources and time often seek engineering partners to design the complete system for a new process or to keep their existing process up-to-date and running smoothly. Brooks' solutions-based approach to solving customer applications is ideal.

Brooks' Solutions Group can provide various plans including expert application advice and engineering, ready-to-assemble "kits" and complete, integrated, turnkey systems. We have also developed unique direct liquid injection vaporization systems, manifold systems, precise measurement solutions for dosing applications, and more.

### Solutions for OEMs

Many Brooks Instrument products are ideal for OEM customers, providing high-performing, cost-effective solutions. Current Brooks OEM customers include medical device equipment manufacturers, analyzer manufacturers, suppliers of gas blending equipment, vacuum pump makers, and industrial processing equipment suppliers. Brooks can customize any standard product to meet OEM requirements.

- t Compact thermal mass flow meters and controllers
- t Needle valves for precise flow control
- t Compact pressure regulators
- t Flow controllers for variable upstream or downstream pressures
- t Custom variable area glass tube assemblies available for your unique applications
- t Customized variable area, thermal mass and Coriolis flow controllers
- t Private labeling available

# Level Measurement



Robust magnetic level gauges from Brooks provide reliable and continuous liquid level measurement through the use of a proven magnetic float technology that does not require external power. As a result, plant engineers can continue to monitor material levels despite planned or unplanned power loss. Optional alarms and transmitters are available to permit remote monitoring as well.

Brooks magnetic level gauges feature sealed measurement chambers constructed from stainless steel, PVC, PPH, PVDF or PTFE that enable reliable level measurement of a wide assortment of liquids including those that are corrosive, toxic or otherwise hazardous. Because the only moving part in contact with the fluid is the float, these instruments are exceptionally rugged and durable. Many process connection options are available, further enhancing application flexibility.

## Type 810 Mechanical Level Gauge

The type 810 magnetic level gauge allows you to measure liquid levels directly – even corrosive or dangerous liquids – in vessels or pressurized tanks. The design of the type 810 ensures good accuracy, excellent reliability, and safe use.

The type 810 mechanical level gauge measures liquid level (or liquid/liquid interface) over ranges from as short as 1 foot (0.3 m) to as long as 20 feet (6 m), and longer with multiple sections of instruments. Applications include product tank monitoring, feed water heaters, condensate and separator systems, cryogenic gases, effluent tanks, and more.

## MC1000 Continuous Level Transmitter

This economical level instrument features a ball float on a stainless steel rod that can be insertion-mounted or mounted in a bypass chamber. The MC1000 comes with either flanged or threaded tank connections, providing flexible mounting options. Its 4 - 20 mA transmitter can be provided in standard, explosion proof or intrinsically safe configurations with or without HART. The maximum measurement range is 10 feet (3 m) and measurement resolution is 0.6" (15 mm).

Type	Model	Temperature	Pressure psig (bar)	Connection	Output	Construction
Level	810	0-100	0-400 (400)	Flanged/threaded/ welded	Alarm &/or 4 - 20 mA, HART (IS or XP)	304L SS, 316L SS, PVC, PVDF, PPH, PTFE
Level	811	0-100	0-180 (180)	Flanged/threaded/ welded	Alarm &/or 4 - 20mA, HART (IS or XP)	304L SS, 316L SS, PVC, PVDF, PPH, PTFE
Continuous Level	MC1000	N/A	N/A	Flanged/threaded	4 - 20mA, HART (IS or XP)	316 SS, PVC, PVDF



ANV/ANH Point Level Switch



MR783 Multi-Point Level Switch

Point level switches are designed to detect level variations and activate alarms based on one or multiple level points. They can be used for normal, corrosive or hazardous liquids and are certified explosion proof or intrinsically safe. The ANV point level switches are certified and used in highly demanding nuclear power plant applications. Certified material, NACE and radiography options are available to meet customer specifications.

### ANV/ANH Point Level Switch

The vertical Series ANV and horizontal Series ANH level switches are designed to detect level variations and activate alarms accordingly. They can be used for normal, corrosive or hazardous liquids and are certified explosion proof or intrinsically safe. Certified material, NACE and radiography options are available to meet customer specifications.

### MR783 Multi-Point Level Switch

This multi-point level switch is compact, making it easy to mount in multiple locations on a tank. With versatile construction (316SS, PVC or PVDF), the MR783 is certified explosion proof or intrinsically safe and is capable of indicating more than one level per tank and triggering alarms accordingly.

Type	Model	Temperature	Pressure psig (bar)	Connection	Output	Construction
Point Level - Vertical Mount	ANV	To 350 °C / 660 °F	1450 (100)	Flanged/threaded	Alarm (IS or XP), up to 2 switches	Carbon steel, 316 SS
Point Level - Horizontal Mount	ANH	To 350 °C / 660 °F	1450 (100)	Flanged/threaded	Alarm (IS or XP), up to 2 switches	Carbon steel, 316 SS
Point Level - Top Mount	MR783	To 100 °C / 212 °F	N/A	Flanged/threaded	Alarm (IS or XP), up to 2 switches	316 SS, PVC, PVDF





Flomega™



Oval Gear Meter

## Flomega™ measures and controls very low flows

Flomega™ liquid flow meters and flow controllers use thermal mass flow technology to accurately measure and control liquids, especially very low flows of liquid from 2 to 1000 grams per hour. They are weatherproof and certified for use in hazardous areas.

Type	Model	Full-Scale Capacity	Accuracy	Max. Pressure psig (bar)	Input/Output	Power Supply
Liquid Mass Flow Controller/Meter	5881/91	30 - 100 g/hr	0.5% FS	5800 (400)	0 - 5 Vdc, 4 - 20 mA	15 - 24 Vdc
Liquid Mass Flow Controller/Meter	5882/92	200 - 1000 g/hr	0.5% FS	5800 (400)	0 - 5 Vdc, 4 - 20 mA	15 - 24 Vdc

## Oval gear positive displacement meter for high-viscosity liquids

Brooks' oval gear positive displacement meters are ideal for highly viscous liquids in applications where accuracy and repeatability are critical.

Type	Model	Capacity - Water	Accuracy Rate	Max. Pressure psig (bar)	Temperature	Construction
Oval Gear Meter	BM01/02	2 - 500 lph/ 0.53 - 132 gph	1%	150 (10)	-29 - 66 °C -20 - 150 °F	316 SS, PPS
Oval Gear Meter	BM04/50	60 - 21,000 lph/ 15 - 5500 gph	0.5%	800 (55)	-29 - 120 °C -20 - 248 °F	Aluminum, 316 SS, PPS



## Application experts at your service

Backed by outstanding support, Brooks is committed to assuring that our customers receive the ideal solution for their application. We make it easy to locate a sales representative and get technical assistance, training services and more. Our instruments are top in the industry, but it's our application experience and support services that set us apart from the competition:

- t Brooks factory-trained support
- t 24/7 telephone support
- t Worldwide coverage
- t Primary standard calibration equipment at every Service Center
- t NIST and NMI traceability to ensure accuracy and reliability

**Start-Up Service:** Need help getting your new flow products installed properly? Brooks' on-site start-up service will set up your flow products, then test them to make sure they are operating perfectly in your application.

**Extended Warranties:** For uninterrupted support and peace of mind, extended warranties may be purchased at any time within the original warranty period or after major repair in a Brooks Service Facility.

**Preventive Maintenance Programs:** For ongoing process accuracy and reliability, we offer a number of preventive maintenance programs. Brooks also offers annual calibration service for all devices and full rebuild/refurbishment.

**Advanced Replacement Options:** To minimize operational downtime, Brooks can provide advanced replacement devices for certain models in exchange for your existing device.

**Training Services:** Brooks encourages customers to take advantage of our excellent training programs such as "The Basics of Flow Measurement," "Calibration" and "Maintenance." We also offer customized, hands-on programs to fit your specific needs. Both factory and on-site training are available.

BrooksInstrument.com

Find your local Brooks application specialist  
by visiting [BrooksInstrument.com/FindYourLocalSpecialist](http://BrooksInstrument.com/FindYourLocalSpecialist)



# BROOKS<sup>®</sup> INSTRUMENT

Application Experience  
Beyond Measure

## Global Headquarters

Brooks Instrument  
407 West Vine Street  
Hatfield, PA 19440-0903 USA  
Toll-free (USA): 888-554-FLOW  
T: 215-362-3700  
F: 215-362-3745  
BrooksAM@BrooksInstrument.com

## Europe, Middle East & Africa

Brooks Instrument  
Neonstraat 3  
6718 WX Ede  
Netherlands  
T: +31 (0) 318 549300  
F: +31 (0) 318 549309  
BrooksEU@BrooksInstrument.com

## Germany

Brooks Instrument  
Zur Wetterwarte 50  
Gebäude 337/B  
01109 Dresden  
Germany  
T: +49 (0) 351 2152 040  
F: +49 (0) 351 2152 0425

## China

Brooks Instrument China  
Room 203, Building 6  
No. 1888 Xin Jin Qiao Road  
Jin Qiao E.P.Z. Pu Dong  
Shanghai 201206 China  
T: +86 (21) 3872 0770  
F: +86 (21) 3872 0771

## India

Brooks Instrument India Pvt Ltd  
301, 3rd Floor  
A to Z Industrial Estate  
Ganpatrao Kadam Marg  
Lower Parel, Mumbai 400 013  
Maharashtra, India  
T: +91 (22) 6627 0780  
F: +91 (22) 6627 0780 Extn: 8

## Japan

Brooks Instrument Japan  
1-4-4 Kitasuna Koto-Ku  
Tokyo, 136-0073 Japan  
T: +81 (3) 5633 7100  
F: +81 (3) 5633 7101  
BrooksAS@BrooksInstrument.com

## Singapore

Brooks Instrument Singapore  
18 Boon Lay Way  
#04-136 Tradehub 21  
Singapore 609966  
T: +65 6595 5168  
F: +65 6595 5169  
BrooksAS@BrooksInstrument.com

## Korea

Brooks Instrument Korea  
D-406, Bundang Techno Park  
#151 Yatap-dong, Bundang ku  
Sungnam-Shi  
Kyungki-do, Korea 463-050  
T: +82 (31) 708 2521  
F: +82 (31) 708 2595



Scan the QR code to  
get Brooks' contact  
info directly on your  
mobile device.

Download the app  
at [getscanlife.com](http://getscanlife.com)

Votre contact Brooks Instrument :  
**Serv'Instrumentation**  
**Z.I Broteau Nord**  
**69540 Irigny**  
**France**  
**Tél : +33 (0)4 78 51 47 50**  
**Fax : +33 (0)4 78 51 59 96**  
**Email : [e-serv@servinstrumentation.fr](mailto:e-serv@servinstrumentation.fr)**  
**Web : [www.servinstrumentation.fr](http://www.servinstrumentation.fr)**

publication are presented for information purposes only, and while effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available on request. We reserve the right to modify or improve the designs or specifications of our products at any time without notice. For the latest Brooks product specifications, view the "Products" section of our website.